

Dominion PX Specifications Chart

Model	Switched Receptacles	Input Voltage Phase	Maximum Amperage	Rack Space	Plug Type	Dimension (WxDxH)	Weight
DPCR8-15	8 x NEMA 5-15R	120 VAC, 1 PH	15 amps 1800 VA	1U	NEMA 5-15P	17.32" x 6.57" x 1.73"; 440 x 167 x 44mm	8.0 lbs; 3.6 kg
DPCS12-20	12 x NEMA 5-15R	120 VAC, 1 PH	20 amps 2400 VA	Zero U	NEMA 5-20P	2.24" x 1.97" x 49.33"; 57 x 50 x 1253mm	7.7 lbs; 3.5 kg
DPCR20-20	20 x NEMA 5-15R	120 VAC, 1 PH	20 amps 2400 VA	2U	NEMA 5-20P	17.32" x 10.79" x 3.46"; 440 x 274 x 88mm	12.8 lbs; 5.8 kg
DPCS20-20	20 x NEMA 5-15R	120 VAC, 1 PH	20 amps 2400 VA	Zero U	NEMA 5-20P	2.24" x 1.97" x 70.71"; 57 x 50 x 1796mm	11.2 lbs; 5.1 kg
DPCS20-20L	20 x NEMA 5-15R	120 VAC, 1 PH	20 amps 2400 VA	Zero U	NEMA L5-20P	2.24" x 1.97" x 70.71"; 57 x 50 x 1796mm	11.2 lbs; 5.1 kg
DPCR20-30L	20 x NEMA 5-15R	120 VAC, 1 PH	30 amps 3600 VA	2U	NEMA L5-30P	17.32" x 10.79" x 3.46"; 440 x 274 x 88mm	13.4 lbs; 6.1 kg
DPCS20-30L	20 x NEMA 5-15R	120 VAC, 1 PH	30 amps 3600 VA	Zero U	NEMA L5-30P	2.24" x 1.97" x 73.58"; 57 x 50 x 1869mm	11.8 lbs; 5.4 kg
DPCR8A-20L6	8 x IEC 60320 C13	208 VAC, 1 PH	20 amps 4160 VA	1U	NEMA L6-20P	17.32" x 6.57" x 1.73"; 440 x 167 x 44mm	8.0 lbs; 3.6 kg
DPCS20A-20L6	20 x IEC 60320 C13	208 VAC, 1 PH	20 amps 4160 VA	Zero U	NEMA L6-20P	2.24" x 1.97" x 70.79"; 57 x 50 x 1798mm	11.2 lbs; 5.1 kg
DPCR20A-30L6	20 x IEC 60320 C13	208 VAC, 1 PH	30 amps 6240 VA	2U	NEMA L6-30P	19.02" x 10.51" x 3.46"; 483 x 267 x 88mm	14.7 lbs; 6.7 kg
DPCS20A-30L6	20 x IEC 60320 C13	208 VAC, 1 PH	30 amps 6240 VA	Zero U	NEMA L6-30P	2.24" x 1.97" x 78.70"; 57 x 50 x 1999mm	11.9 lbs; 5.4 kg
DPCR8A-16	8 x IEC 60320 C13	230 VAC, 1 PH	16 amps 3680 VA	1U	IEC 60309 6H-P	17.32" x 6.57" x 1.73"; 440 x 167 x 44mm	8.0 lbs; 3.6 kg
DPCS12A-16	12 x IEC 60320 C13	230 VAC, 1 PH	16 amps 3680 VA	Zero U	IEC 60309 6H-P	2.24" x 1.97" x 49.33"; 57 x 50 x 1253mm	7.7 lbs; 3.5 kg
DPCS20A-16	20 x IEC 60320 C13	230 VAC, 1 PH	16 amps 3680 VA	Zero U	IEC 60309 6H-P	2.24" x 1.97" x 70.79"; 57 x 50 x 1798mm	11.3 lbs; 5.2 kg
DPCR20A-32	20 x IEC 60320 C13	230 VAC, 1 PH	32 amps 7360 VA	2U	IEC 60309 6H-P	17.32" x 10.79" x 3.46"; 440 x 274 x 88mm	13.4 lbs; 6.1 kg
DPCS20A-32	20 x IEC 60320 C13	230 VAC, 1 PH	32 amps 7360 VA	Zero U	IEC 60309 6H-P	2.24" x 1.97" x 73.58"; 57 x 50 x 1869mm	11.3 lbs; 5.2 kg

Sensors

DPX-T1 * Temperature sensor * 3 m cord	DPX-T1H1 * Temperature and humidity sensor * 3 m cord	DPX-T2H2 * Dual temperature and humidity sensors 3 m apart * 6 m cord	DPX-ENVHUB 4 port (RJ-12) sensor expansion hub
---	--	--	--

Cord length 15 ft (4.5 m). Add 3.5" / 88mm (2U) to the height of the Zero U units for the Dominion PX power cable's radius of curvature. Allow approximately 4.5" (114mm) additional depth to accommodate the 1U and 2U brackets, device plugs and cables. Meter accuracy +/- < 5%. Tool-less button mounting included for Zero U models. Mounting brackets are included for 1U and 2U models.

The same plugs and receptacles may go by a variety of names and standards. For example, IEC 60309 was formerly IEC 309 and various other standards, such as BS 4343 and BS EN 60309 are based on IEC 60309 and may also be referred to as CEE plugs or as commando connectors. Also, IEC 60320 was formerly IEC 320. Parts from various manufacturers are compatible if they meet the same standards.



DPCR20-20



DPCR8-15













DPX-T1H1









DPX-ENVHUB

Dominion PX – Plugs and Receptacles Configuration Chart

NEMA

RECEPTACLE	PLUG	RECEPTACLE	PLUG
 <p>NEMA 5-15R 15 Ampere 125 Volt</p>	 <p>NEMA 5-15P 15 Ampere 125 Volt</p>	 <p>NEMA 5-20R 20 Ampere 125 Volt</p>	 <p>NEMA 5-20P 20 Ampere 125 Volt</p>
 <p>NEMA L5-20R 20 Ampere 125 Volt Locking</p>	 <p>NEMA L5-20P 20 Ampere 125 Volt Locking</p>	 <p>NEMA L5-30R 30 Ampere 125 Volt Locking</p>	 <p>NEMA L5-30P 30 Ampere 125 Volt Locking</p>
 <p>NEMA L6-20R 20 Ampere 250 Volt Locking</p>	 <p>NEMA L6-20P 20 Ampere 250 Volt Locking</p>	 <p>NEMA L6-30R 30 Ampere 250 Volt Locking</p>	 <p>NEMA L6-30P 30 Ampere 250 Volt Locking</p>

IEC

RECEPTACLE	PLUG	RECEPTACLE	PLUG
 <p>IEC 60309 6H-R 20 Ampere 250 Volt UL/CSA 16 Ampere 230 Volt European CE Mark</p>	 <p>IEC 60309 6H-P</p>	 <p>IEC 60309 6H-R 30 Ampere 250 Volt UL/CSA 32 Ampere 230 Volt European CE Mark</p>	 <p>IEC 60309 6H-P</p>
 <p>IEC 60320 C-13 15 Ampere 250 Volt UL/CSA 10 Ampere 250 Volt International</p>	 <p>IEC 60320 C-14</p>		

Call 1.800.724.8090 or visit Raritan.com/Remote-Power-Management